

Available online at www.sciencedirect.com**SciVerse ScienceDirect**

Procedia Engineering 57 (2013) 504 – 514

**Procedia
Engineering**www.elsevier.com/locate/procedia11th International Conference on Modern Building Materials, Structures and Techniques,
MBMST 2013

Elastic Lateral-Torsional Buckling of Simply Supported Hot-Rolled Steel I-Beams with Random Imperfections

Zdeněk Kala *

Department of Structural Mechanics, Faculty of Civil Engineering, Brno University of Technology, Veveří st. 95, 602 00 Brno, Czech Republic

Abstract

The paper deals with the problem of lateral beam buckling of simply supported hot-rolled I-beams under major axis bending. The bending stability problem is analysed by consideration the minor axis bending and torsion equations. Both perfect straight beams and beams with initial imperfections are considered. The mathematical solutions are derived, based on a non-linear stability model. The attention is paid to virtual computer experiments of beams with initial random imperfections. Realizations of initial imperfections are simulated, applying the numerical simulation method Latin Hypercube Sampling. Statistical characteristics of the majority of imperfections were found by experimental research. The influence of the beam length on the mean value and standard deviation of load carrying capacity is analysed. The screening based sensitivity analysis method is applied. The principal imperfections affecting lateral beam buckling strength are discussed.

© 2013 The Authors. Published by Elsevier Ltd. Open access under [CC BY-NC-ND license](http://creativecommons.org/licenses/by-nc-nd/4.0/).

Selection and peer-review under responsibility of the Vilnius Gediminas Technical University

Keywords: beam, bending, lateral buckling, stability, steel, imperfection, deflection, twist, resistance, failure.

1. Introduction

Structural steel members can be classified as tension or compression members, beams, beam-columns, torsion members or plates [1]. The beams subjected to flexure typically have strength and stiffness in the plane associated with bending about their major principal axis (in the plane in which the loads are applied) much greater than in the plane associated with bending about their minor principal axis [2]. Unless these members are properly braced against lateral deflection and twisting, they are subject to failure by lateral beam buckling prior to the attainment of the full in-plane capacity [3].

The aim of the present paper is a stochastic analysis of bending stability problem of simply supported hot-rolled I-beam with initial random imperfections. Theoretical development and practical applications related to the uncertainty, safety and reliability were obtained both in the field of civil engineering, and in multi-disciplinary approaches including Bayesian methods [4], fuzzy logic models [5], and fuzzy and interval analysis [6], geotechnical engineering and geomechanics [7], geostatistics [8, 9], inspection [10] and quality control [11], optimization under uncertainty [12], probabilistic materials analysis [13], risk analysis [14], vibration [15], reliability-based design [16], reliability-based optimization and control [17], reliability theory [18], statistical design analysis, stochastic computational mechanics, and stochastic finite elements [19], stochastic fracture mechanics [20], system identification [21], system reliability [22], and sensitivity analysis [23, 24] etc.

* Corresponding author.

E-mail address: kala.z@fce.vutbr.cz

2. Buckling of straight beams with equal end moments

The first theoretical studies of the bending stability problem for a beam with thin rectangular cross-section were elaborated, independently of each other, by [25] and [26], namely as early as in 1899. It was S. P. Timošenko [27] for the first time who presented the analysis of lateral beam buckling of horizontally loaded thin-walled steel beams which was of significance for practice. He dealt with the stability of plane bending of the beam with I-cross-section, taking into consideration the bending toughness of flanges at buckling from the plane of primary deformation. Articles from the last period are e.g. [28, 29, 30, 31].

The bending stability problem of hot-rolled I-beam with equal end moment is presented in Fig. 1 and Fig. 2.




Fig. 1. Lateral beam buckling of simply supported straight I-beam with equal end moment




Fig. 2. 3D illustration of lateral beam buckling

The ends of the beam are assumed to be prevented from lateral deflection v and from twisting φ

$$(v)_0 = (v)_L = 0, \quad (\varphi)_0 = (\varphi)_L = 0, \quad (1)$$

but they are free to rotate laterally

$$\left(\frac{\partial^2 v}{\partial x^2} \right)_0 = \left(\frac{\partial^2 v}{\partial x^2} \right)_L = 0, \quad \left(\frac{\partial^2 \varphi}{\partial x^2} \right)_0 = \left(\frac{\partial^2 \varphi}{\partial x^2} \right)_L = 0. \quad (2)$$

The elastic critical moment M_{cr} of the beam shown in Fig. 1 and Fig. 2 can be determined by finding a deflected and twisted position which is one of equilibrium.

Internal minor axis bending moment $M_{cr} \varphi$ is caused by applied bending moment M_{cr} and twisted position φ , see Fig. 3. The value of internal bending moment $M_{cr} \varphi$ is calculated from the moment equilibrium on deformed beam element, see Fig. 3. The bending moment M_{cr} at any point along the length of the deformed beam is the vector sum of moments $M_{cr} \sin(\varphi)$ and $M_{cr} \cos(\varphi)$. As the value of φ is very low, it can be written approximately $M_{cr} \sin(\varphi) \approx M_{cr} \varphi$ and $M_{cr} \cos(\varphi) \approx M_{cr}$.

The torsional moment $M_{cr} dv/dx$ is caused by applied bending moment M_{cr} and deflection v , see Fig. 4. The value of internal torsional moment $M_{cr} dv/dx$ is calculated from the moment equilibrium on deformed beam element, see Fig. 4. The bending moment M_{cr} at any point along the length of the deformed beam is the vector sum of moments $M_{cr} \sin(\varphi_z)$ and $M_{cr} \cos(\varphi_z)$ where $\tan(\varphi_z) = dv/dx$. Due to the very low value of φ_z it can be written $M_{cr} \sin(\varphi_z) \approx M_{cr} dv/dx$ and $M_{cr} \cos(\varphi_z) \approx M_{cr}$.

The differential equilibrium equation of bending of the beam is

$$E I_z \frac{d^2 v}{dx^2} = -M_{cr} \varphi, \quad (3)$$

where E is modulus of elasticity and I_z is second moments of area about axis z .

The differential equilibrium equation of torsion of the beam is

$$E I_\omega \frac{d^3 \varphi}{dx^3} - G I_t \frac{d\varphi}{dx} = -M_{cr} \frac{dv}{dx}, \quad (4)$$

where G is shear modulus, I_ω is warping section constant, and I_t is torsion constant. For large torsion, the functions $\cos(\varphi)$ and $\sin(\varphi)$ can be approximated by $\cos(\varphi) \approx 1 - \varphi^2/2$ and $\sin(\varphi) \approx \varphi - \varphi^3/6$.




Fig. 3. The bending equilibrium of twisted position of the beam





Fig. 4. The bending equilibrium of the beam deflection position

Fig. 5. Components of applied bending moment M_{cr}

Both components of applied bending moment M_{cr} are shown in Fig. 5.

When both (3) and (4) are satisfied at all points along the beam, than the deflected position is

$$v = a_{vc} \sin\left(\frac{\pi x}{L}\right) \quad (5)$$

and the twisting position is

$$\varphi = a_{\varphi c} \sin\left(\frac{\pi x}{L}\right) \quad (6)$$

where amplitude a_{vc} is the function of amplitude $a_{\varphi c}$

$$a_{vc} = a_{\varphi c} \frac{M_{cr} L^2}{\pi^2 EI_z}. \quad (7)$$

By substituting (5) and (6) for (4), we obtain

$$\begin{aligned} -EI_{\omega} a_{vc} \frac{\pi^5 EI_z}{M_{cr} L^5} \cos\left(\frac{\pi x}{L}\right) - GI_t a_{vc} \frac{\pi^3 EI_z}{M_{cr} L^3} \cos\left(\frac{\pi x}{L}\right) = \\ -M_{cr} a_{vc} \frac{\pi}{L} \cos\left(\frac{\pi x}{L}\right). \end{aligned} \quad (8)$$

The elastic critical moment M_{cr} for lateral beam buckling will be obtained from (8) as

$$M_{cr} = \pi \sqrt{\frac{EI_z GI_t}{L}} \sqrt{1 + \frac{\pi^2 EI_{\omega}}{L^2 GI_t}} \quad (9)$$

3. Buckling of imperfect beams with equal end moments

The elastic behaviour of simply supported imperfect beam under equal and opposite end moments M can be analysed with using the minor axis bending and torsion equations.

$$EI_z \frac{d^2 v}{dx^2} = -M(\varphi + \varphi_0), \quad (10)$$

$$EI_{\omega} \frac{d^3 \varphi}{dx^3} - GI_t \frac{d\varphi}{dx} = -M \left(\frac{dv}{dx} + \frac{dv_0}{dx} \right), \quad (11)$$

where v_0 is initial curvature and φ_0 is initial twist. The ends of the beam are assumed to be prevented from lateral deflection v (1) and from twisting φ (2). The close form solution of (10) and (11) can be solved according to, e.g., [1] and/or [29]. Let us consider the initial imperfection in affine position to buckled shapes (5) and (6) so that the initial curvature v_0 and twist φ_0 are the sine functions

$$v_0 = a_{v0} \sin\left(\frac{\pi x}{L}\right) \quad (12)$$

$$\varphi_0 = a_{\varphi 0} \sin\left(\frac{\pi x}{L}\right) \quad (13)$$

where amplitudes a_{v0} and $a_{\varphi 0}$ are considered, according to (7), as

$$a_{v0} = a_{\varphi 0} \frac{M_{cr} L^2}{\pi^2 EI_z}. \quad (14)$$

The solution of (10) and (11) which satisfied the boundary conditions (1) and (2) is given by

$$v = a_v \sin\left(\frac{\pi x}{L}\right) \quad (15)$$

$$\varphi = a_\varphi \sin\left(\frac{\pi x}{L}\right) \quad (16)$$

where amplitudes a_v and a_φ are

$$a_v = a_{v0} \frac{M}{M_{cr} - M} \quad (17)$$

$$a_\varphi = a_{\varphi0} \frac{M}{M_{cr} - M} \quad (18)$$

The maximum longitudinal stress σ_x in the beam is the sum of the stresses due to the major axis bending, minor axis bending, and warping.

$$\sigma_{x,\max} = \frac{M}{W_y} - \frac{EI_z}{W_z} \frac{\partial^2 v}{\partial x^2} - E \frac{\partial^2 \varphi}{\partial x^2} \omega_{\max} \quad (19)$$

where ω_{\max} is maximum of the sectorial co-ordinate of the point used in Vlasov's model for non uniform torsion [32]. For doubly symmetric I-beam is $\omega_{\max} = bh/4$. W_y is section modulus about axis y , and W_z is section modulus about axis z . The failure of imperfect beam is initiated in $x = L/2$ when maximum longitudinal stress $\sigma_{x,\max}$ causes yield strength f_y . The load carrying capacity (elastic resistance) M_R can be derived from (19) and calculated as

$$M_R = - \frac{\sqrt{4D_1^2 + (D_4 + D_5)^2 + 4D_1(D_4 - 2M_{cr}D_3)}}{4M_{cr}W_z} + \frac{2D_1 + D_4 + D_5}{4M_{cr}W_z} \quad (20)$$

where

$$\begin{aligned} D_1 &= f_y M_{cr} W_y W_z \\ D_2 &= M_{cr} W_z + P_z |a_{v0}| W_y \\ D_3 &= M_{cr} W_z - P_z |a_{v0}| W_y \\ D_4 &= 2P_z^2 I_y |a_{v0}| \\ D_5 &= 2M_{cr} D_2 \\ P_z &= \pi^2 \frac{EI_z}{L^2} \end{aligned} \quad (21)$$

4. Stochastic analysis of load carrying capacity






The load carrying capacity M_R is, in general, a random quantity the variability of which can be studied by applying the numerical simulation methods of type Monte Carlo. 10 000 simulation runs of the Latin Hypercube Sampling method were used. Experimentally obtained material and geometrical characteristics of steel products made by a dominant Czech producer, see [13] were applied to the problem solved. For non-measured quantities, the study was based on data obtained from technical literature; e.g., statistical characteristics of Young's modulus are given in [33]. Input quantities are amplitude a_{v0} of initial curvature, yield strength f_y , cross-sectional height h , cross-sectional width b , web thickness t_w , flange thickness t_f and Young modulus E . Let us remark that the experimental data are important input information regarding the models of reliability analysis, based on the failure probability calculations [34, 35].

The hot-rolled IPE 240 cross-section was used. All the input factors X_i , given synoptically in Table 1, are statistically independent of one another.







Table 1. Input random quantities

Characteristic	Mean value	Standard deviation
Cross-sectional height h	240 mm	1.0616 mm
Cross-sectional width b	120 mm	1.1842 mm
Web thickness t_1	6.2 mm	0.2421 mm
Flange thickness t_2	9.8 mm	0.4494 mm
Yield strength f_y	297.3 MPa	16.8 mm
Young's modulus E	210 GPa	10 GPa
Amplitude a_{v0}	0	0.76533 L

The principal variable affecting lateral beam buckling strength is the distance between lateral braces. In Fig. 6 to Fig. 23, there is presented the influence of beam length L (unbraced length) on its load carrying capacity.

Fig. 6. Load carrying capacity vs initial curvature for $L = 1.0$ mFig. 7. Load carrying capacity vs initial curvature for $L = 1.5$ mFig. 8. Load carrying capacity vs initial curvature for $L = 2.0$ mFig. 9. Load carrying capacity vs initial curvature for $L = 2.5$ mFig. 10. Load carrying capacity vs initial curvature for $L = 3.0$ m

The central question of screening in the context of modelling of lateral beam buckling and computer simulation is: Which factors among the input imperfections are really important? The random influence of amplitude of initial curvature a_{v0} on load carrying capacity is evident from Fig. 6 to Fig. 21. The maximum influence is noticeable for the beam lengths $L = 3.0$ m and $L = 3.3$ m. The beam with $L = 3.0$ m has a nondimensional slenderness according to EUROCODE 3 calculated as, $\bar{\lambda} = 0.83$ and the beam with $L = 3.5$ m has $\bar{\lambda} = 0.96$. The complete analysis includes Fig. 6 to Fig. 21 plus other $6 \times 16 = 96$ figures. Such a screening method is very clear and relatively economical, when compared with the methods of variance based sensitivity analysis. As a drawback, these screening methods do not quantify higher order interactions among input imperfections [36]. Another question arises: How the beam length change influences the load carrying capacity? It is evident from Fig. 22 that the mean value of load carrying capacity decreases with increasing beam length.

Fig. 11. Load carrying capacity vs initial curvature for $L = 3.5$ mFig. 12. Load carrying capacity vs initial curvature for $L = 4.0$ mFig. 13. Load carrying capacity vs initial curvature for $L = 4.5$ mFig. 14. Load carrying capacity vs initial curvature for $L = 5.0$ mFig. 15. Load carrying capacity vs initial curvature for $L = 5.5$ mFig. 16. Load carrying capacity vs initial curvature for $L = 6.0$ m

The analysis of the beam length influence on the standard deviation of load-carrying capacity is depicted in Fig. 23. The maximum of the std. deviation curve was obtained for $L = 2.9$.

The stability design of beams and columns is generally treated in international design codes by using – r all buckling cases – the same curves used for column buckling (Taras 2010). More general results could be obtained using the normalized elastic slenderness $\bar{\lambda}_{LT,el}$ for lateral beam buckling [29]. According to EUROCODE 3, non-dimensional $\bar{\lambda}_{LT}$ shall be determined as

$$\bar{\lambda}_{LT} = \sqrt{\frac{W_{pl,y} f_{n,y}}{M_{cr}}} \quad (22)$$

where $W_{pl,y}$ is plastic section modulus and $f_{n,y}$ is characteristic value of yield strength.




Fig. 17. Load carrying capacity vs initial curvature for $L = 6.5$ m




Fig. 18. Load carrying capacity vs initial curvature for $L = 7.0$ m




Fig. 19. Load carrying capacity vs initial curvature for $L = 7.5$ m




Fig. 20. Load carrying capacity vs initial curvature for $L = 8.0$ m






Fig. 21. Load carrying capacity vs initial curvature for $L = 8.5$ m

Fig. 22. Mean value of load carrying capacity vs beam length L Fig. 23. St. deviation of load carrying capacity vs beam length L

5. Conclusion

Thin-walled elements as beams, columns, trusses or as sheeting rails are extensively used in structural engineering, ranging from residential buildings to industrial construction. Thin-walled structures such as I-section members typically exhibit a detrimental imperfection sensitivity, which drastically reduces their ultimate load bearing capacity compared to their theoretical strength. The problems of bending stability problem of simply supported hot-rolled I-beam with equal end moment were described in the present paper. First, an analysis of idealized perfect straight elastic beams was carried out. The attention was concentrated, above all, on a detailed description of buckled shape geometry which was one of equilibrium. The elastic critical moment M_{cr} for lateral beam buckling was determined. However, a perfectly straight beam may yield before the elastic critical moment M_{cr} is reached because of the combination effect of in-plane bending stresses and initial imperfections. In general, the beam has many imperfections both geometrical and material which can decrease its load carrying capacity. The random influence of initial curvature and initial twist on load carrying capacity was analyzed in the paper. There were determined the beam lengths for which the influence of the imperfections mentioned is maximum.

In further research work, the initial curvature and initial twist will be considered to be statistically independent quantities. The standard deviation of the initial curvature can be more accurately considered under [29]. The standard deviation can be derived according to the limit of the initial curvature, see Fig. 24.




Fig. 24. Possible maximum value of the initial deformation

The initial twist can be approximately $\pm 1^\circ$. Is the influence of initial twist very low or could it be totally neglected? This hypothesis should be verified by a computer model based on shell finite elements and nonlinear computation methods.

Acknowledgements

The article was elaborated within the framework of projects TAČR TA01020307 and VG20132015109 and GAČR P105/12/0314.

References

- [1] Trahair, N. S. 1977. The behaviour and design of steel structures. John Wiley and Sons, Ltd. 1977. 320 p.
- [2] Galambos, T. V. 1998. Stability design criteria for metal structures. John Wiley and Sons, Ltd. 1998. 911 p.
- [3] Ziemian, R. D. 2010. Stability design criteria for metal structures. John Wiley and Sons, Ltd. 2010. 1078 p.
- [4] Strauss, A.; Frangopol, D. M.; Kim, S. 2008. Use of monitoring extreme data for the performance prediction of structures: Bayesian updating. Engineering Structures 30(12), pp. 3654–3666.
- [5] Torno, S.; Torano, J.; Menendez, M.; Gent, M.; Velasco, J. 2011. Mathematical and fuzzy logic models in prediction of geological and geomechanical properties of rock mass by excavation data on underground works, Journal of Civil Engineering and Management 17(2), pp. 197–206.

- [6] Chen, T. Y.; Tsao, Ch. Y. 2008. The interval-valued fuzzy TOPSIS method and experimental analysis, *Fuzzy Sets and Systems* 159(11), pp. 1410–1428.
- [7] Tumonis, L.; Kacianauskas, R.; Norkus, A.; Zilioniene, D. 2012. Comparison study of spherical and multi-spherical particles under cyclic uniaxial compression, *Journal of Civil Engineering and Management* 18(4), pp. 537–545.
- [8] Lark, R.M. 2012. Towards soil geostatistics, *Spatial Statistics* 1, pp. 92–99.
- [9] Skuodi, Š.; Norkus, A.; Tumonis, L.; Amšiejus, J.; Aksamitauskas, Č. 2013. Experimental and numerical investigation of sand compression peculiarities, *Journal of Civil Engineering and Management* 19(1), pp. 78–85.
- [10] Silva, A.; Dias, J. L.; Gaspar, P. L.; de Brito, J. 2013. Statistical models applied to service life prediction of rendered facades, *Automation in Construction* 30, pp. 151–160.
- [11] Rafiei, K.; Kavussi, A.; Yasrobi, S. 2012. Construction quality control of unbound layers based on stiffness modulus criteria, *Journal of Civil Engineering and Management* 18(1), pp. 5–13.
- [12] Atkočiūnas, J.; Venskus, A. 2011. Optimal shakedown design of frames under stability conditions according to standards, *Computers and Structures* 89(3–4), pp. 435–443.
- [13] Kala, Z.; Melcher, J.; Puklický, L. 2009. Material and geometrical characteristics of structural steels based on statistical analysis of metallurgical products, *Journal of Civil Engineering and Management* 15(3), pp. 299–307.
- [14] Ke, Y.; Wang, S.; Chan Albert, P. C. 2012. Risk management practice in China's Public-Private Partnership projects, *Journal of Civil Engineering and Management* 18(5), pp. 675–684.
- [15] Kala, J.; Salajka, V.; Hradil, P. 2012. Investigation of eigenvalue problem of water tower construction interacting with fluid, *Journal of Vibroengineering* 14(3), pp. 1151–1159.
- [16] Kala, Z. 2007. Stability problems of steel structures in the presence of stochastic and fuzzy uncertainty, *Journal of Thin-Walled Structures* 45(10–11), pp. 861–865.
- [17] Zavadskas, E. K.; Turskis, Z.; Tamosaitiene, J. 2011. Selection of construction enterprises management strategy based on the SWOT and multi-criteria analysis, *Archives of Civil and Mechanical Engineering* 11(4), pp. 1063–1082.
- [18] Kowal, Z. 2011. The formation of bar space structures supported by the system reliability theory, *Archives of Civil and Mechanical Engineering* 11(1), pp. 115–133.
- [19] Shang, S.; Yun, G. J. 2013. Stochastic finite element with material uncertainties: Implementation in a general purpose simulation program, *Finite Elements in Analysis and Design* 64, pp. 65–78.
- [20] Reddy, R. M.; Rao, B. N. 2008. Stochastic fracture mechanics by fractal finite element method, *Computer Methods Applied Mechanics and Engineering* 198(3–4), pp. 459–474.
- [21] Baruch, I. S.; Lopez, R. B.; Guzman, J.-L. O.; Flores, J. M. 2008. A fuzzy-neural multi-model for nonlinear systems identification and control, *Fuzzy Sets and Systems* 159(20), pp. 2650–2667.
- [22] Savage, G. J.; Son, Y. K. 2011. The set-theory method for systems reliability of structures with degrading components, *Reliability Engineering and System Safety* 96(1), pp. 108–116.
- [23] Kala, Z. 2012. Geometrically non-linear finite element reliability analysis of steel plane frames with initial imperfections, *Journal of Civil Engineering and Management* 18(1), pp. 81–90.
- [24] Kala, Z.; Gottvald, J. 2012. Sensitivity analysis of tangential digging forces of the bucket wheel excavator SchRs 1320 for different terraces, *Journal of Civil Engineering and Management* 18(5), pp. 609–620.
- [25] Prandtl, L. 1899. *Kipperscheinungen*, Dissertation, München, 1899.
- [26]] Michell, A.G. 1899. Elastic stability of long beam under transverse forces, *Philosophical Magazine* 48.
- [27] Timošenko, S.P. 1905. *Izvēstija S.-Pēterburgskogo politēchničeskogo instituta* 4, 1905.
- [28] Taras, A.; Greiner, R. 2008. Torsional and flexural torsional buckling – A study on laterally restrained I-sections, *Journal of Constructional Steel Research* 64(7–8), pp. 725–731.
- [29] Taras, A.; Greiner, R. 2010. New design curves for lateral–torsional buckling—Proposal based on a consistent derivation, *Journal of Constructional Steel Research* 64(7–8), pp. 648–663.
- [30] Rebelo, C.; Lopes, N.; Simoes da Silva, L.; Nethercot, D.; Vila Real, P.M.M. 2010. Statistical evaluation of the lateral–torsional buckling resistance of steel I-beams, Part 1: Variability of the Eurocode 3 resistance model, *Journal of Constructional Steel Research* 65(4), pp. 818–831.
- [31] Simoes da Silva, L.; Rebelo, C.; Nethercot, D.; Marques, L.; Simoes R.; Vila Real, P.M.M. 2010. Statistical evaluation of the lateral–torsional buckling resistance of steel I-beams, Part 2: Variability of steel properties, *Journal of Constructional Steel Research* 65(4), pp. 832–849.
- [32] Vlasov, V. Z. 1959. *Thin walled elastic beams*, Moscow.
- [33] Soares, G.C. 1988. Uncertainty modelling in plate buckling, *Structural Safety* 5(1), pp. 17–34.
- [34] Melcher, J.; Škaloud, M.; Kala, Z.; Karmazinová, M. 2009. Sensitivity and statistical analysis within the elaboration of steel plated girder resistance, *Advanced Steel Construction* 5(2) pp. 120–126.
- [35] Kala, Z.; Puklický, L.; Omishore, A.; Karmazinová, M.; Melcher, J. 2010. Stability problems of steel-concrete members composed of high-strength materials, *Journal of Civil Engineering and Management* 16(3), pp. 352–362.
- [36] Saltelli, A.; Chan, K.; Scott, E. M. 2000. *Sensitivity analysis*. John Wiley and Sons, Ltd. 2000. 475 p.